



SIRAH H-250

Installation

Ceiling, Surface or recessed mounting. (For recess mounting use accessories ST-21 & ST-28, see page 10)

Optical part

Polycarbonate transparent diffuser. Pictograms (see page 41)



Design

Poly carbonate housing and diffuser, manufactured in conformity with Norms EN60598-2-22 & UNE 20-392-93. LAMP included.



Model	Type	IP	Weight	Autonomy	Lumens	Battery	Lamp	Code
SIRAH H-75	NM	42	0,6	1	70	2.4 V 1.5A*h	6 W(G5)	4501000000
SIRAH H-100	NM	42	0,6	1	95	2.4 V 1.5A*h	6 W(G5)	4501006270
SIRAH H-102	NM	42	0,7	2	105	4.8 V 1.5A*h	6 W(G5)	4501007400
SIRAH H-103	NM	42	0,7	3	74	(2.4 V 1.6A*h)x2	6 W(G5)	4501006280
SIRAH H-180	NM	42	0,6	1	150	3.6 V 1.5A*h	6 W(G5)	4501006290
SIRAH H-182	NM	42	0,7	2	155	6.0 V 1.6A*h	6 W(G5)	4501007410
SIRAH H-250	NM	42	0,7	1	206	4.8 V 1.5A*h	6 W(G5)	4501006300
SIRAH H-252	NM	42	0,7	2	243	6.0 V 1.8A*h	PL-11W(2G7)	4501007420
SIRAH H-380	NM	42	0,7	1	365	6.0 V 1.5A*h	PL-11 W(2G7)	4501006310
SIRAH H-500	NM	42	0,7	1	480	6.0 V 1.8A*h	PL-11W(2G7)	4501007390

*NM: NON MAINTAINED