



LYRA L-100E



LYRA LC-150E

Installation


Wall or ceiling surface mounting.

Design

Poly carbonate housing and diffuser, manufactured in conformity with Norms EN60598-2-22 & UNE 20-392-93. LAMP INCLUDED

Optical part

Polycarbonate transparent diffuser. Pictograms (see page 41)



MODELS IP 65



Model	Type	IP	Weight	Autonomy	Lumens	Battery	Lamp	Code
LYRA L-100 E	NM	65	1.1	1	120	2.4 V 1.5A*h	8 W (G5)	4501006060
LYRA L-300 E	NM	65	1.3	1	276	6.0 V 1.5A*h	8 W (G5)	4501006080
LYRA L-153 E	NM	65	1.3	3	143	3.6 V 4.0A*h	8 W (G5)	4501006090
LYRA L-400 E	NM	65	1.3	1	334	6.0 V 1.5A*h	PL-11 W (2G7)	4501006260
LYRA L-500 E	NM	65	1.3	1	481	3.6 V 4.0A*h	PL-11 W (2G7)	4501006110
LYRA L-302 E	NM	65	1.3	2	266	3.6 V 4.0A*h	8 W (G5)	4501006130
LYRA LM-200 E	M	65	1.2	1	160	3.6 V 1.5A*h	8 W (G5)	4501007020
LYRA LM-203 E	M	65	1.3	3	150	(3.6 V 1.6A*h)x2	8 W (G5)	4501007030
LYRA LM-210	M	42	1.2	1	160	3.6 V 1.5A*h	8 W (G5)	4501007170
LYRA LC-150 E	C	65	1.3	1	149	3.6 V 1.5A*h	8 W (G5)	4501006150
LYRA LC-153 E	C	65	1.4	3	144	3.6 V 4.0A*h	8 W (G5)	4501006160
LYRA LC-250 E	C	65	1.4	1	246	6.0 V 1.5A*h	8 W (G5)	4501006180
LYRA L-100 E AT	NM	65	1.3	1	120	6.0 V 1.8A*h	8 W (G5)	4501007520
LYRA L-150 E AT	NM	65	1.3	1	156	6.0 V 1.8A*h	8 W (G5)	4501007530
LYRA L-300 E AT	NM	65	1.3	1	276	6.0 V 1.8A*h	8 W (G5)	4501006140
LYRA L-400 E AT	NM	65	1.3	1	334	6.0 V 1.8A*h	PL -11W (2G7)	4501007540
LYRA L-500 E AT	NM	65	1.3	1	481	6.0 V 1.8A*h	PL -11W (2G7)	4501007550
LYRA LC-100 E AT	C	65	1.3	1	105	6.0 V 1.8A*h	8 W (G5)	4501007560
LYRA LC-150 E AT	C	65	1.3	1	149	6.0 V 1.8A*h	8 W (G5)	4501007570
LYRA LC-250 E AT	C	65	1.3	1	246	6.0 V 1.8A*h	8 W (G5)	4501007580
LYRA LC-300 E AT	C	65	1.3	1	300	6.0 V 1.8A*h	8 W (G5)	4501007250

*NM: NON MAINTAINED / M: MAINTAINED/ *C: COMBINED 2 TUBES / *AT: AUTO TEST