

# Serie SIRAH LED

Emergency lighting



SIRAH H-100 LED



## Installation

Ceiling, Surface or recessed mounting. (For recess mounting use accessories ST-21 & ST-28, see page 10)

## Optical part

Polycarbonate transparent diffuser.  
Pictograms (see page 41)



## Design

Poly carbonate housing and diffuser, manufactured in conformity with Norms EN60598-2-22 & UNE 20-392-93.

PATENT LED LAMP, easily replaceable and provides a stable illumination.

LAMP included.



| Model           | Type | IP | Weight | Autonomy | Lumens | Battery      | Lamp          | Code       |
|-----------------|------|----|--------|----------|--------|--------------|---------------|------------|
| SIRAH H-100 LED | NM   | 42 | 0.7    | 1        | 120    | 4,8 V 1.5A*h | 2,4 W LED(G5) | 4502002590 |
| SIRAH H-150 LED | NM   | 42 | 0.7    | 1        | 160    | 4,8 V 1.5A*h | 2,4 W LED(G5) | 4502002570 |
| SIRAH H-200 LED | NM   | 42 | 0.7    | 2        | 190    | 4,8 V 1.5A*h | 2,4 W LED(G5) | 4502002580 |
| SIRAH H-102 LED | NM   | 42 | 0.7    | 2        | 120    | 4,8 V 1.5A*h | 2,4 W LED(G5) | 4502002590 |
| SIRAH H-152 LED | NM   | 42 | 0.7    | 2        | 160    | 4,8 V 1.5A*h | 2,4 W LED(G5) | 4502002570 |
| SIRAH H-202 LED | NM   | 42 | 0.7    | 2        | 190    | 4,8 V 1.5A*h | 2,4 W LED(G5) | 4502002580 |
| SIRAH H-103 LED | NM   | 42 | 0.7    | 3        | 120    | 4,8 V 1.5A*h | 2,4 W LED(G5) | 4502002590 |
| SIRAH H-153 LED | NM   | 42 | 0.7    | 3        | 160    | 4,8 V 1.5A*h | 2,4 W LED(G5) | 4502002570 |

\*NM: NON MAINTAINED