



LYRA L-250 LED



Installation

Wall or ceiling surface mounting.




Design

Poly carbonate housing and diffuser, manufactured in conformity with Norms EN60598-2-22 & UNE 20-392-93.

PATENT LED LAMP, easily replaceable and provides a stable illumination. LAMP included.

Optical part

Polycarbonate transparent diffuser. Pictograms (see page 41)



LED lamp radiator



LED linear lamp



Model	Type	IP	Weight	Autonomy	Lumens	Battery	Lamp	Code
LYRA L-100 LED	M/NM	42	1.1	1	120	6.0 V 0.8A*h	3.6 W LED (G5)	4502002680
LYRA L-100 E LED	M/NM	65	1.1	1	120	6.0 V 0.8A*h	3.6 W LED (G5)	4502002690
LYRA L-250 LED	M/NM	42	1.1	1	270	6.0 V 0.8A*h	3.6 W LED (G5)	4502000020
LYRA L-250 E LED	M/NM	65	1.1	1	270	6.0 V 0.8A*h	3.6 W LED (G5)	4502000010
LYRA L-253 LED	M/NM	42	1.1	3	187	6.0 V 1.5A*h	3.6 W LED (G5)	4502000030
LYRA L-253 E LED	M/NM	65	1.1	3	187	6.0 V 1.5A*h	3.6 W LED (G5)	4502000040
LYRA SIGN LED	AC/DC	42	1.0		220	-	3.6 W LED (G5)	4502002320
LYRA SIGN E LED	AC/DC	65	1.0		220	-	3.6 W LED (G5)	4502002330
LYRA L-100 LED AT	M/NM	42	1.1	1	120	6.0 V 0.8A*h	3.6 W LED (G5)	4502002700
LYRA L-100 E LED AT	M/NM	65	1.1	1	120	6.0 V 0.8A*h	3.6 W LED (G5)	4502002710
LYRA L-250 LED AT	M/NM	42	1.1	1	270	6.0 V 0.8A*h	3.6 W LED (G5)	4502002430
LYRA L-250 E LED AT	M/NM	65	1.1	1	270	6.0 V 0.8A*h	3.6 W LED (G5)	4502002440

*NM: NON MAINTAINED / *M: MAINTAINED / *AT: AUTO TEST