

Serie LYRA IP42

Emergency lighting



LYRA L-100



LYRA LC-150

Installation

Wall or ceiling surface mounting.

Design


Poly carbonate housing and diffuser, manufactured in conformity with Norms EN60598-2-22 & UNE 20-392-93.

LAMP INCLUDED

Optical part

Polycarbonate transparent diffuser.

Pictograms (see page 41)



MODELS IP 42



Model	Type	IP	Weight	Autonomy	Lumens	Battery	Lamp	Code
LYRA L-100	NM	42	1.1	1	120	2.4 V 1.5A*h	8 W (G5)	4501006010
LYRA L-300	NM	42	1.3	1	276	6.0 V 1.5A*h	8 W (G5)	4501006070
LYRA L-153	NM	42	1.3	3	143	3.6 V 4.0A*h	8 W (G5)	4501006020
LYRA L-400	NM	42	1.3	1	334	6.0 V 1.5A*h	PL-11 W (2G7)	4501006030
LYRA L-500	NM	42	1.3	1	481	3.6 V 4.0A*h	PL-11 W (2G7)	4501006100
LYRA L-302	NM	42	1.3	2	266	3.6 V 4.0A*h	8 W (G5)	4501006120
LYRA LM-200	M	42	1.2	1	160	3.6 V 1.5A*h	8 W (G5)	4501007000
LYRA LM-203	M	42	1.3	3	150	(3.6 V 1.6A*h)X2	8 W (G5)	4501007010
LYRA LM-210	M	42	1.3	1	160	3.6 V 1.5A*h	PL-11W (2G7)	4501007160
LYRA LC-150	C	42	1.3	1	149	3.6 V 1.5A*h	8 W (G5)	4501006040
LYRA LC-153	C	42	1.3	3	144	3.6 V 4.0A*h	8 W (G5)	4501006050
LYRA LC-250	C	42	1.3	1	246	6.0 V 1.5A*h	8 W (G5)	4501006170

LYRA L-100 AT	NM	42	1.3	1	120	6.0 V 1.8A*h	8 W (G5)	4502002900
LYRA L-150 AT	NM	42	1.3	1	156	6.0 V 1.8A*h	8 W (G5)	4501007490
LYRA L-300 AT	NM	42	1.3	1	276	6.0 V 1.5A*h	8 W (G5)	4501006140
LYRA L-400 AT	NM	42	1.3	1	334	6.0 V 1.8A*h	PL-11W (2G7)	4502002880
LYRA L-500 AT	NM	42	1.3	1	481	6.0 V 1.5A*h	PL-11W (2G7)	4502002890
LYRA LC-300 AT	C	42	1.3	1	276	6.0 V 1.5A*h	8 W (G5)	4501006980
LYRA LC-100 AT	C	42	1.3	1	105	6 V 1.8A*h	8 W (G5)	4501007500
LYRA LC-150 AT	C	42	1.3	1	149	6 V 1.8A*h	8 W (G5)	4502002910
LYRA LC-250 AT	C	42	1.3	1	246	6 V 1.8A*h	8 W (G5)	4501007510

*NM: NON MAINTAINED / M: MAINTAINED/ *C: COMBINED 2 TUBES / *AT: AUTO TEST